

003B.00024.U1 (US)

C3041

Patent Application Papers Of:

Richard Chadbourne

For: Modular Lug Block Assembly

Modular Lug Block Assembly

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to electrical connectors and, more particularly, to an electrical connection block assembly.

2. Brief Description Of Prior Developments

Power stud blocks are generally known in the art. For example, Marathon Special Products sells 600 Volt power stud blocks under the catalog numbers 1422122 and 1423122. Power stud blocks are generally used for AC or DC power distribution, such as for a DC circuit in a telecom application. Power stud blocks can be provided in two pole or three poll configurations.

There is a desire to provide an electrical power connection block which is smaller in size than conventional electrical power connection blocks. There is also a desire to provide an electrical power connection block which has modular components to allow multiple different types of connection blocks to be manufactured with use of common components.

SUMMARY OF THE INVENTION

In accordance with one aspect of the present invention, an electrical power connection block housing is provided including a first housing piece and a second housing piece. The first housing piece forms at least a portion of a first exterior side of the block housing. An

interior side of the first housing piece has a first slot shaped bus bar mounting area. The second housing piece is connected to the first housing piece. The second housing piece has a portion with a first side located directly opposite the interior side of the first housing piece and a second slot shaped bus bar mounting area on the second side of the second housing piece. The first and second housing pieces form a first bus bar receiving area with the first and second bus bar mounting areas located generally opposite each other on opposite sides of the receiving area for capturing a bus bar therebetween.

In accordance with another aspect of the present invention, an electrical power connection block housing is provided including a first housing piece, a second housing piece, and a third housing piece. The first housing piece forms at least a portion of a first side of the block housing. The first housing piece has a first interlock connection section. The second housing piece has a first side with a second interlock connection section directly interconnected with the first interlock connection section and a second side with a third interlock connection section. The third housing piece has a first side with a fourth interlock connection section directly interconnected with the third interlock connection section. The housing pieces form bus bar receiving areas therebetween. The first and third interlock connection sections are substantially a same size and shape.

In accordance with one method of the present invention, a method of assembling an electrical power connection block assembly is provided including steps of locating

electrical bus bars between pairs of housing pieces of the connection block, a middle one of the housing pieces having two of the bus bars located against opposite respective sides of the middle housing piece; and
5 intermeshing mating projections and recesses of the housing pieces with adjacent housing pieces to interlock the housing pieces with each other.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and other features of the present invention are explained in the following description,
10 taken in connection with the accompanying drawings, wherein:

Fig. 1 is a top, front and right side perspective view of an electrical connection block assembly incorporating features of the present invention shown connected to
15 electrical conductors and located on another member;

Fig. 2 is a top, front and right side perspective view of the assembly shown in Fig. 1 without the electrical conductors and with the cover located in an exploded
20 position;

Fig. 3 is an exploded perspective view of some of the components of the assembly shown in Fig. 2;

Fig. 4 is an exploded bottom, front and left side perspective view of some of the components of the
25 assembly shown in Fig. 2;

Fig. 5 is an exploded bottom, rear and right side perspective view of the components of the assembly shown in Fig. 2;

Fig. 6 is a cross sectional view of the first interlock connection section of the first housing piece;

Fig. 7 is an exploded top, left side and front side perspective view of the housing;

5 Fig. 8 is a perspective view of one of the bus bars used in the assembly shown in Fig. 2;

Fig. 9 is an exploded perspective view of an alternate embodiment of the present invention;

Fig 10 is a perspective view of an alternate embodiment of the bus bar shown in Fig. 8; and

Fig 11 is a perspective view of another alternate embodiment of the bus bar shown in Fig. 8.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Fig. 1, there is shown a perspective view of an electrical power connection block assembly 10 incorporating features of the present invention shown attached to electrical conductors A, B, C and D and located on top of a mounting member E. Although the present invention will be described with reference to the embodiments shown in the drawings, it should be understood that the present invention can be embodied in many alternate forms of embodiments. In addition, any suitable size, shape or type of elements or materials could be used.

25 The block assembly 10 generally comprises a housing 8 and electrical bus bars 9a, 9b (see Fig. 3; also referred to as bus bars 9). The housing 8 generally comprises a container 12 and a cover 14. However, in an alternate

embodiment, the cover might not be provided. In the embodiment shown, the block assembly 10 is a two pole block assembly. However, as described below, features of the present invention can be incorporated into a three or more poll block assembly. In the embodiment shown, the block assembly 10 is for a DC power distribution circuit. However, in an alternate embodiment, the present invention could be used as an AC power distribution circuit.

Conductors A and C are connected to each other inside the block assembly 10 by bus bar 9a and are connected to supply electricity from a battery. Conductors B and D are connected to each other inside the block assembly 10 by bus bar 9b and are connected as a return to the battery. However, the conductors A-D could be connected to any suitable components. In addition, more or less than four conductors could be connected by the block assembly.

The mounting member E could be any suitable type of component, such as a metal sheet member. The mounting member E comprises holes F therethrough. Fasteners (not shown) such as screws can be used to fixedly attach the block assembly 10 to the mounting member E by being screwed into the holes F and being located in the fastener receiving areas 16 of the container 12. However, In alternate embodiments, any suitable type of system for mounting the block assembly 10 to another component could be provided.

Referring also to Figs. 2-7, the container 12 generally comprises three housing pieces 18, 20 and 22. However, in alternate embodiments, the container 12 could be comprised of more or less than three housing pieces. The

first and third housing pieces 18, 22 are substantially mirror images of each other except at their bottom sections as will be described in further detail below. The first and third housing pieces 18, 22 form the outer sides of the container 12. The first housing piece 18 forms a left side. The third housing piece 22 forms a right side. The terms "right", "left", "top", "bottom", "front" and "rear" are used herein for reference only. The second housing piece 20 is sandwiched between the first and third housing pieces. Thus, the second housing piece 20 forms a middle piece of the container 12.

The first housing piece 18 generally comprises a bottom section 24, a side section 26, a front section 28 and a rear section 30. The bottom section 24 comprises a first interlock connection section 25. As seen best in Fig. 6, the first interlock connection section 25 comprises a side edge of the bottom section 24 having two pairs of bottom slots 32, top slots 34, and cover sections 36. However, more or less than two pairs could be provided. In addition, the first interlock connection section could have any suitable type of size or shape. For example, rather than molding the cover section 36 over the top slot, a piece of non-integrally-molded flat insulating material can be placed over the top slot.

In the embodiment shown, the top slots 34 are located over the bottom slots 32. The bottom slots 32 extend into the side edge a further distance than the top slots 34. The top and bottom slots are connected to each other, but the top and bottom slots are partially horizontally offset from each other in each pair. The cover sections 36 are located over the top slots 34. In an alternate embodiment the cover sections 36 might not

be provided. Front and rear ends of the bottom section 24 also comprise slots 38, 40.

The side section 26 has an interior facing side which comprises a bus bar mounting area. In the embodiment shown, the bus bar mounting area generally comprises a first projection 42 and a second projection 44. The first projection 42 has a general C shape and extends inward from the interior side. The second projection has a general reversed C shape and extends inward from the interior side. In the embodiment shown, the first and second projections are partially vertically offset from each other.

The C shape and reversed C shape each form a slot 46, 48 which are vertically offset from each other. The slots 46, 48 form receiving areas for one of the side edges of one of the bus bars 9a, 9b as will be described in further detail below. In alternate embodiments, the bus bar mounting areas could have any suitable type of shape. For example, the bus bar mounting area might not comprise projections, but instead could comprise recessed slots. Alternatively, the projections could have any suitable type of shape, so long as the bus bar mounting area is adapted to receive a side edge of the bus bar 9. An exterior side of the first housing piece 18 at the side section 26 comprises the fastener mounting areas 16. The front section 28 comprises a recess 50. The rear section 30 comprises a recess 52. The top side of the side section 26, front section 28 and rear section 30 form part of a cover mounting lip 54 (see Figs. 2 and 4).

As best seen in Figs. 3, 5 and 7, the second housing piece 20 generally comprises a bottom section 56, a middle section 58, a front section 60 and a rear section

62. The bottom section 56 comprises a second interlock connection section 64 and a third interlock connection section 66. The third interlock connection section 66 is substantially identical to the first interlock connection section 25. However, in alternate embodiments, the first and third interlock connection sections could have different sizes or shapes. As seen best in Fig. 3, the third interlock connection section 66 comprises a side edge of the bottom section 56 having two pairs of bottom slots 32, top slots 34, and cover sections 36. However, more or less than two pairs could be provided. In addition, the third interlock connection section could have any suitable type of size or shape.

The second interlock connection section 64 comprises a side edge of the bottom section 56 having two pairs of bottom projections 68, top projections 70 and, recesses 72, 74 between the pairs. However, more or less than two pairs could be provided. In addition, the second interlock connection section could have any suitable type of size or shape. In the embodiment shown, the top projections 70 are located over the bottom projections 68. The bottom projections 68 extend outward at the side edge a further distance than the top projections 70. The top and bottom projections are partially horizontally offset from each other in each pair. The second interlock connection section 64 is sized and shaped to mate with the first interlock connection section 25.

The middle section 58 has a side which faces the first housing piece 18 which comprises a bus bar mounting area. In the embodiment shown, the bus bar mounting area generally comprises a first projection 76 and a second projection 78. The first projection 76 has a reversed

general C shape and extends from the side. The second projection has a general C shape and extending from the side. In the embodiment shown, the first and second projections are partially vertically offset from each other. The C shape and reversed C shape form slots 80, 82 which are vertically offset from each other. The slots 80, 82 form receiving areas for one of the side edges of one of the bus bars 9 as will be described in further detail below.

As seen best in Fig. 3, the middle section 58 also has an opposite side which comprises a bus bar mounting area and which faces the third housing piece 22. In the embodiment shown, the bus bar mounting area on the opposite side generally comprises a first projection 84 and a second projection 86. The first projection 84 has a general C shape and extends outward from the side. The second projection has a general reversed C shape and extends outward from the side. In the embodiment shown, the first and second projections are partially vertically offset from each other.

The C shape and reversed C shape each form a slot 88, 90 which are vertically offset from each other. The slots 88, 90 form receiving areas for one of the side edges of one of the bus bars 9 as will be described in further detail below. In alternate embodiments, the bus bar mounting areas could have any suitable type of shape. For example, the bus bar mounting area might not comprise projections, but instead could comprise recessed slots. Alternatively, the projections could have any suitable type of shape, so long as the bus bar mounting area is adapted to receive a side edge of the bus bar 9. The

lateral sides of the front and rear ends of the bottom section 56 also comprises slots and projections.

The front section 60 comprises two recesses 92a, 92b. The rear section 62 comprises two recesses 94a, 94b. The top side of the front section 60 and rear section 62 form part of the cover mounting lip 54. The middle section 58 has fastener holes 96 into its top side. As seen with reference to Figs. 1 and 2, when the second housing piece 20 is connected to the first housing piece 18, the recesses 50 and 92a form an aperture 98 which allows the conductor D to pass through the housing 8. Likewise, the recesses 52 and 94a form an aperture 100 which allows the conductor B to pass through the housing 8.

The third housing piece 22 generally comprises a bottom section 102, a side section 104, a front section 106 and a rear section 108. The bottom section 102 comprises a fourth interlock connection section 110. The fourth interlock connection section 110 is substantially identical to the second interlock connection section 64. However, in alternate embodiments, the second and fourth interlock connection sections could have different sizes and shapes.

As seen best in Fig. 7, the fourth interlock connection section comprises a side edge of the bottom section 102 having two pairs of bottom projections 68, top projections 70 and, recesses 72, 74 between the pairs. However, more or less than two pairs could be provided. In addition, the fourth interlock connection section could have any suitable type of size or shape. In the embodiment shown, the top projections 70 are located over the bottom projections 68. The bottom projections 68 extend outward at the side edge a further distance than

the top projections 70. The top and bottom projections are partially horizontally offset from each other in each pair. The fourth interlock connection section 110 is sized and shaped to mate with the third interlock connection section 66.

The side section 104 has an interior facing side which comprises a bus bar mounting area. The bus bar mounting area on the side section 104 is substantially identical to the bus bar mounting area on the side of the middle section 58 of the middle housing piece 20 which faces the first housing piece 18. However, in alternate embodiments, the two bus bar mounting areas could have different sizes and shapes.

In the embodiment shown, the bus bar mounting area in the side section 104 generally comprises a first projection 112 and a second projection 114. The first projection 112 has a general C shape and extends inward from the interior side. The second projection 114 has a general reversed C shape and extends inward from the interior side. In the embodiment shown, the first and second projections are partially vertically offset from each other. The C shape and reversed C shape each form a slot 116, 118 which are vertically offset from each other. The slots 116, 118 form receiving areas for one of the side edges of one of the bus bars 9 as will be described in further detail below.

In alternate embodiments, the bus bar mounting area on the side section 104 could have any suitable type of shape. For example, the bus bar mounting area might not comprise projections, but instead could comprise recessed slots. Alternatively, the projections could have any suitable type of shape, so long as the bus bar mounting

area is adapted to receive a side edge of the bus bar 9. An exterior side of the third housing piece 22 at the side section 104 comprises the fastener mounting areas 16. The front section 106 comprises a recess 120. The rear section 108 comprises a recess 122. The top side of the side section 104, front section 106 and rear section 108 form part of the cover mounting lip 54. As seen with reference to Figs. 1 and 2, when the second housing piece 20 is connected to the third housing piece 22, the recesses 92b and 120 form an aperture 124 which allows the conductor C to pass through the housing 8. Likewise, the recesses 94b and 122 form an aperture 126 which allows the conductor A to pass through the housing 8.

The housing pieces 18, 20 and 22 are adapted to be assembled to each other as shown in Figs. 1, 2 and 4. The first interlock connection section 25 and the second interlock connection section 64 matingly interlock with each other. Likewise, the third interlock connection section 66 and the fourth interlock connection section 110 matingly interlock with each other. This forms the container 12. The cover 14 can be placed on the container lip 54 and fasteners 128 (see Fig. 1) can fixedly attach the cover 14 to the center section 58 of the middle piece 20. However, the cover 14 might not be provided. The housing pieces 18, 20 and 22 are preferably retained with each other by fasteners (not shown) located in the fastener receiving areas 16 and attached to the member E. However, in alternate embodiments, any suitable means could be provided for fixedly retaining the housing pieces with each other separate from the member E, such as the cover 14 for example.

Before the housing pieces 18, 20 and 22 are attached to the member E, the conductors A-D or preferably attached to connectors 130a-130d which, in turn, are fixedly attached to the bus bars 9. The connectors 130a-130d generally comprise a first section 132 and a second section 134. The first section 132 is adapted to be crimped or compressed onto one of the conductors A-D. The second section 134 has holes therethrough for mounting on posts of the bus bars 9. However, in alternate embodiments, the block assembly 10 could be used with conductors having any suitable type or shape of connectors thereon.

Referring also to Fig. 8, each bus bar 9 generally comprises a first section 136, a second section 138, and a connecting section 140. In alternate embodiments, the bus bars could be different from each other. The first section 136 comprises fastening posts 142. The second section 138 comprises fastening posts 144. The fastening posts 142 extend in an opposite direction from the fastening posts 144. Although the embodiment shown shows two fastening posts for each of the first and second sections 136, 138, each section might comprise more or less than two fastening posts. In addition, rather than fastening posts, the bus bar could comprise any suitable means for fixedly and stationarily attaching the connectors 130 thereto.

One alternate embodiment of the bus bar is shown in Fig. 10. In this alternate embodiment, the bus bar 170 comprises a flat block of stock material with two sets 172, 174 of fastener mounting holes 176. The fastener holes have enlarged counter-bored sections 178 which are adapted to receive a head of a fastener, such as a stud

or screw, for clearance. Each set 172, 174 has its counter-bored sections 178 on opposite sides of the bus bar. Another alternate embodiment of the bus bar is shown in Fig. 11. In this embodiment the bus bar 180 has
5 tapped or threaded holes 182. This allows the use of screws or bolts instead of nuts on studs.

In the embodiment shown, the first section 136 is vertically offset from the second section 138. The connecting section 140 connects the first section 136 with the second section 138. In this embodiment, the
10 first section 136, second section 138 and connecting section 140 form a general Z shape. However, in alternate embodiments, the sections could form the bus bar in any suitable type of shape. For example, the first and second sections 136, 138 might not be
15 vertically offset from each other. The first and second sections could have notches on their respective top and bottom sides. Alternatively, the first and second sections could have raised sections on their respective top and bottom sides for receiving the second sections
20 134. For such alternatives embodiments, the slots in each of the bus bar mounting areas might not be vertically offset from each other.

The second sections 134 of the connectors 130 are mounted
25 on the posts 142, 144 and the nuts 146 are attached to the posts 142, 144 to fixedly and stationarily attach the connectors 130 to the bus bars 9. As seen best in Figs. 4 and 5, the connectors 130a and 130b are located on top sides of the bus bars 9 and extend towards the rear ends
30 of the bus bars. The connectors 130c and 130d are located on bottom sides of the bus bars 9 and extend towards the front ends of the bus bars. These

connections could be made in a factory the housing pieces being mounted on the piece of equipment E with screws in cavities 16. Conductors A and B could be installed during equipment installation when the electrical power is connected.

With the conductors A-D attached to the connectors 130, and the connectors 130 attached to the bus bars 9a, 9b, the bus bars 9 are placed between the housing pieces 18, 20 and 22. The housing pieces 18, 20 and 22 are then assembled to each other. During assembly, side edges of the bus bars 9 are received in the slots of the bus bar mounting areas in the housing pieces. The two slots 46 and 80 are located directly opposite each other. The two slots 48 and 82 are located directly opposite each other. The two slots 88 and 116 are located directly opposite each other. The two slots 90 and 188 are located directly opposite each other.

A right side edge of the right bus bar 9a is located in the bus bar receiving area of the third housing piece 22. More specifically, the right side edge of the first section 136 is located in the slot 116, the right side edge of the second section 138 is located in the slot 118, and the right side edge of the connecting section 140 is located between the two projections 112, 114. A left side edge of the bus bar 9a is located in the right side bus bar receiving area of the second housing piece 20. More specifically, the left side edge of the first section 136 is located in the slot 88, the left side edge of the second section 138 is located in the slot 90, and the left side edge of the connecting section 140 is located between the two projections 84, 86. This stationarily traps the bus bar 9a between the housing

pieces 20, 22 at a predetermined fixed location. The top and bottom sides of the bus bar 9a and connectors 130a, 130c are spaced a predetermined distance from the top and bottom sides of the housing 8 to provide a predetermined air clearance.

A left side edge of the left bus bar 9b is located in the bus bar receiving area of the first housing piece 18. More specifically, the left side edge of the first section 136 is located in the slot 46, the left side edge of the second section 138 is located in the slot 48, and the left side edge of the connecting section 140 is located between the two projections 42, 44. A right side edge of the bus bar 9b is located in the left side bus bar receiving area of the second housing piece 20. More specifically, the right side edge of the first section 136 is located in the slot 80, the right side edge of the second section 138 is located in the slot 82, and the right side edge of the connecting section 140 is located between the two projections 76, 78. This stationarily traps the bus bar 9b between the housing pieces 18, 20 at a predetermined fixed location. More specifically, the top and bottom sides of the bus bar 9b and connectors 130b, 130d are spaced a predetermined distance from the top and bottom sides of the housing 8 to provide a predetermined air clearance. The top connectors 130a, 130b can also be removed from the bus bars 9 without removing the bus bars from their connection with the housing pieces 18, 20, 22.

One of the features of the present invention is the use of both lateral sides of the bus bars to mount and entrap the bus bars between the housing pieces. Entrapping the bus bars in a suspended matter enables both sides of the

bus bar to be used. This results in a much smaller electrical power connection block. This can take up less space on the member E. This invention can allow a method of making a factory connection at an OEM that enables the end user to make the power connection with a reliable lug terminal. The two pole lug block body described above consists of merely three molded plastic component housing pieces that interlock with each other trapping the two bus bars suspended in between them. The present invention uses the lateral sides of the bus bars as mounting ears for the bus bars. This can reduce the overall size of the connection block. If a three poll installation is required, then an additional center block 20 and bus bar can be used side by side with the other components.

Another one of the features of the present invention is in regard to the interlocking and keying nature of the interlock connection sections 25, 64, 66 and 110. As noted above, the projections 68 and 70 have different lateral lengths. Likewise, the recesses 32, 34 have different lateral lengths. Thus, when the housing pieces 18, 20 and 22 are connected to each other even if the housing pieces are not precisely flush against each other the overlapping nature of the housing pieces prevent air gaps at the seams between the top side of the bottom sections and the bottom sides of the bottom sections. This prevents a possible incorrect air clearance and oversurface clearance between the bus bars and the member E. However, in alternate embodiments, any suitable type of overlapping of the housing pieces at their connection could be provided.

Another feature of the present invention is in regard to the modular design of the housing pieces 18, 20 and 22. The housing pieces are easily assembled without any special tools. The keying nature of the interlock connection sections 25, 64, 66 and 110 prevent the housing pieces from being incorrectly assembled relative to each other. Referring also to Fig. 9, an alternate embodiment of the electrical power connection block is shown. The embodiment shown is for a three poll connection. Thus, the connection block 150 comprises three electrical bus bars 9a, 9b and 9c, and connection block housing 152.

In this embodiment, the connection block housing 152 generally comprises a first housing piece 154, a second housing piece 156, a third housing piece 158 and a fourth housing piece 160. The first housing piece 154 is identical to the first housing piece 18 of the embodiment shown in Figs. 1-7. The fourth housing piece 160 is identical to the third housing piece 22 of the embodiment shown in Figs. 1-7. The second housing piece 156 and the third housing piece 158 are identical to each other. The second and third housing pieces 156, 158 are identical to the second housing piece 20 of the embodiment shown in Figs. 1-7.

Thus, three housing piece components can be used to form a housing container for either a two pole situation, as in the embodiment shown in Figs. 1-7, or a three poll situation as in the embodiment shown in Fig. 9. This can reduce manufacturing costs and inventory costs. For the three poll situation, a person assembling the housing components merely adds a second one of the middle housing pieces and an additional bus bar.

It should be understood that the foregoing description is only illustrative of the invention. Various alternatives and modifications can be devised by those skilled in the art without departing from the invention. Accordingly, 5 the present invention is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
222